

InterActive™ Respiratory Humidifier



Specification sheet

Intended use

The InterActive respiratory humidifier is intended to heat and humidify respiratory gases in a hospital environment.

Available modes	Invasive	Non-invasive	Manual
Chamber side temperature range	Pre-set to 37°C	Pre-set to 31°C	31°C – 42°C Increments of 1°C
Patient side temperature range	Pre-set to 40°C	Pre-set to 34°C	31°C – 40°C Increments of 1°C
Gas temperature display	Est. temperature at interface	Est. temperature at interface	Patient probe temperature

Environmental	
Operating temperature	18°C to 26°C
Operating Relative Humidity	0% to 80%
Atmospheric pressure	0 to 2,000m
Storage temperature	-18°C to 50°C
Storage Relative Humidity	0% to 80%

Electrical rating	
Supply voltage	220V AC—240V AC / 100V AC—120V AC (Variant dependant. Refer to product label).
Supply frequency	50-60 Hz
Power rating	350 VA
Heated wire power rating	100W
Fuse rating	4A

Dimensions	
Size	(h) 103 mm x (w) 153 mm x (d) 221 mm
Weight	1.8 kg

Classifications	
Protection class, electrical hazard	IEC 60601-1 Class II Medical Electrical Equipment.
IP classification	IPX1
Mode of operation	Continuous use
Sterilisation	Do not sterilise
Applied Parts	This Device uses Type BF Applied Parts. (Temperature Probes and Heated Wire Adapters)

Standards applied	
InterActive complies with the following relevant standards: ISO 80601-2-74 ISO 60601-1+A12 cro SD	

Performance	
Warm up period	45 minutes
Invasive mode	> 33mg/L @ flows between 2 and 70L/min
Non-invasive mode	> 12mg/L @ flows between 2 and 120L/min

Temperature measurement	
Display	°C
Range	25 to 45°C
Resolution	0.1°C
Accuracy	±1°C

Alarm	
Alarm volume	> 50 dbA

SD Card	
Type	Micro SD
Size	16GB*
Read speed	>10MB/s
Class	4





EMC compliance

Emission tests compliance levels

Mains terminal: CISPR16-2-1+A1 230 Vac at 50Hz 115 Vac at 60Hz	Harmonic Current Emissions: IEC61000-3-2 230 Vac at 50Hz 115 Vac at 60Hz
Electromagnetic radiation disturbances – Electric Field: CISPR16-2-3	Voltage fluctuations and flicker: IEC61000-3-3 230 Vac at 50Hz
30 MHz to 1 GHz – Vertical – 230Vac 50Hz 30 MHz to 1 GHz – Horizontal – 230Vac 50Hz 30 MHz to 1 GHz – Vertical – 115Vac 60Hz 30 MHz to 1 GHz – Horizontal – 115Vac 60Hz	

Immunity tests compliance levels

Electrostatic Discharge: IEC61000-4-2 Air discharge at 2kV, 4kV, 8kV and 15kV Contact discharge at 8kV Indirect discharge at 8kV	Surges: IEC61000-4-5+A1 AC input 230Vac 50Hz and 115Vac 60Hz
Radiated RF Electromagnetic Fields: IEC61000-4-3+A1+A2 80 – 2700MHz in all planes	Conducted disturbances induced by RF fields: IEC61000-4-6 3 Vrms 230Vac 50Hz and 115Vac 60Hz
Proximity Fields from RF Wireless Equipment: IEC61000-4-3 +A1+A2 230Vac 50Hz and 115 Vac 60Hz TETRA 400 (380-390MHz) GMRS 460 and FRS460 (430-470MHz) LTE bands 13 and 17 (704-787 MHz) GSM 800/900, TETRA 800, iDEN 820, CDMA 850, LTE Band 5 (800-960 MHz) GSM 1800, CDMA 1900, DECT, LTE Bands 1, 3, 4 & 15, UMTS (1700-1990 MHz) Bluetooth, WLAN 802.11b/g/n, RFID 2450, LTE Band 7 (2400-2570MHz) WLAN 802.11a/n (5100-5700 MHz)	Voltage dips and short interruptions: IEC61000-4-11+A1 AC input 240Vac 50Hz AC input 115Vac 60Hz
Voltage dips and short interruptions: IEC61000-4-11+A1 AC input 240Vac 50Hz AC input 115Vac 60Hz	Voltage dips and short interruptions: IEC61000-4-11+A1 AC input 240Vac 50Hz AC input 115Vac 60Hz

Interact with us



InterActive spec sheet INT ▪ Issue 1 10.24



Intersurgical Ltd, Crane House, Molly Millars Lane, Wokingham, Berkshire, RG41 2RZ, UK
T: +44 (0)118 965 6300 info@intersurgical.com www.intersurgical.com



The manufacturer Intersurgical Ltd is certified to ISO 14001:2015, ISO 9001:2015, ISO 13485:2016 and MDSAP



Please recycle